

# Bronze Globe Valve - PN32

LV 1029

Screwed BSPT, to BS5154 Series B/NM, Renewable PTFE Disc



## Pressure / Temperature Specifications

|             |                |
|-------------|----------------|
| Pressure    | PN32           |
| Temperature | -20°C to 198°C |

## Material Specifications

|               |                       |
|---------------|-----------------------|
| Body          | Gunmetal Bronze       |
| Bonnet        | Forged Brass          |
| Stem          | Brass                 |
| Disc Holder   | Brass                 |
| Disc Ring     | Brass                 |
| Disc          | Glass Reinforced PTFE |
| Disc Nut      | Brass                 |
| Gland         | Brass                 |
| Gland Nut     | Brass                 |
| Packing       | PTFE                  |
| Handwheel     | Aluminium             |
| Handwheel Nut | Brass                 |
| Rating Disc   | Aluminium             |

## Dimensions

| Size | A   | B   | Kv M <sup>3</sup> /H | Kg   |
|------|-----|-----|----------------------|------|
| ½"   | 57  | 95  | 2.00                 | 0.38 |
| ¾"   | 65  | 100 | 5.00                 | 0.54 |
| 1"   | 78  | 114 | 10.00                | 0.84 |
| 1¼"  | 89  | 138 | 16.00                | 1.36 |
| 1½"  | 100 | 159 | 23.00                | 1.76 |
| 2"   | 121 | 170 | 42.00                | 2.62 |

