Thermodynamic Steam Trap (with Air Vent)

Screwed BSPP, Forged Steel Body, Carbon Steel Cover, Stainless Steel Filter

Pressure / Temperature Specifications							
Pressure	PN40						
Maximum Temperature	400°C						

Material Specifications	
1. Body	ASTM A105 Forged Steel
2. Cover	Carbon Steel
3. Filter	304 Stainless Steel
4. Disc	420 Stainless Steel
5. Seat	420 Stainless Steel

Dimen	sions		
Size	1/2"	3/4"	1"
L1	95	95	95
Н	40	40	40
H2	42	42	42
Kg	1.8	1.7	1.6

(Kg/h)														
-				П	П		П			П	П			Ì
-		+	\dashv	+						+	H			
-			\Box	\blacksquare						\prod	П		Ш	
		++	+	+	-				\vdash	+	H		Ш	
1000 -			Ш											-
800 -		\pm		#		Ė					Ħ			
600 -		\blacksquare	П	H		F					1		\Box	
400 -		\blacksquare							1	1			Ш	
300 -		+	Ш	\perp				1					Ш	
200 -		\pm		I									Ш	
_		Ш		$\downarrow \downarrow$									Ш	
			1											
100 - 80 -		\forall												
60 -	1	+	\blacksquare							H			H	
40 -													Ш	
30 -				Ш										
			\parallel											
Kapasite 00														
	1 7	1 7		IT	11	1	1 T		1 T	I T	ιT	1	1 1	

Note: Differential pressure is the difference between inlet pressure and outlet pressure of the steam trap. Maximum operating backpressure must not exceed 80% of the upstream pressure





