

# Brass Ball Valve - Locking Lever



LV 2300

Screwed BSPP, Nickel Plated Body, Brass Ball & Stem, PTFE Seats, Full Bore, Locking Lever. Note: Padlock Sold Separately.



Pressure / Temperature Specifications	
Pressure	PN40
Temperature	-40°C to 170°C

Material Specifications		
1.	Body	Nickel Plated Brass
2.	Seat	PTFE
3.	Ball	Chrome Plated Brass
4.	End Cap	Nickel Plated Brass
5.	Stem	Nickel Plated Brass
6.	Gland Nut	Nickel Plated Brass
7.	Nut	GEOMET
8.	Gland Seal	PTFE
9.	Washer	PTFE
10.	Handle	PVC Coated Steel

Dimensions							
Size	I	L	C	A	H	CH	Kg
1/4"	12	45	22.5	82	39.5	20	0.21
3/8"	12	45	22.5	82	39.5	20	0.21
1/2"	15.5	59	29.5	100	43	25	0.33
3/4"	17	64	32	120	50.5	31	0.5
1"	21	81	40.5	120	54.5	40	0.84
1 1/4"	23	93	46.5	158	76	49	1.2
1 1/2"	23	102	51	158	82	54	1.64
2"	26.5	121	60.5	158	89	68.5	2.67

