

Ductile Iron Ball Valve - Flanged Table E

Flanged BS10 Table E, Ductile Iron 2 Piece Body, Chromed Brass Ball, Brass Stem, PTFE Seats, Lever Operated



Pressure / Temperature Specifications	
Pressure	PN16
Gas Temperature	-10°C to 70°C
Liquid Temperature	-10°C to 100°C

Material Specifications	
1. Body	EN GJS 400-15 Epoxy Coated Ductile Iron
2. Flange	EN GJS 400-15 Epoxy Coated Ductile Iron
3. Ball	CuZn40Pb2 Chrome Plated Brass
4. Ball Seat	Reinforced PTFE
5. Stem	CuZn40Pb2 Brass
6. Sliding Washer	PTFE
7. Ring	CuZn40Pb2 Brass
8. O-ring	NBR
9. Lever	Epoxy Coated Carbon Steel
10. Stop Plate	Galvanized Carbon Steel
11. Spring Washer	Galvanized Carbon Steel

Dimensions			
DN	3"	DN	3"
P	76	J	70
A	180	n°xØq	4x9
H	165	E	20
H1	118	S	17
B	280	Nm*	70
C	200	Kv	947.00
ISO	F07	Kg	15.5

*In order to choose the correct actuator, we recommend multiplying the Nm figure by a safety factor of 1.5

