

# Forged Stainless Steel Gate Valve - Screwed BSPT

LV 6615

Screwed **BSPT**, Class 800, F316L Stainless Steel Body, Trim 12 BB OS & Y,  
Design to AP602, Tested to API 598



## Pressure / Temperature Specifications

|             |                               |
|-------------|-------------------------------|
| Pressure    | CL 800                        |
| Temperature | Contact Sales for Information |

## Material Specifications

|    |                    |                  |
|----|--------------------|------------------|
| 1  | Body               | A182 F316L       |
| 2  | Seat               | A182 F316        |
| 3  | Disc               | A182 F316+STL    |
| 4  | Stem               | A182 F316        |
| 5  | Gasket             | 316SS + Graphite |
| 6  | Bonnet             | A182 F316L       |
| 7  | Bonnet Bolt        | A193 B8M         |
| 8  | Stem Packing       | Graphite         |
| 9  | Bolt               | A193 B8M         |
| 10 | Gland              | 316SS            |
| 11 | Gland Flange       | A182 F316        |
| 12 | Nut                | A194 8M          |
| 13 | Stem Nut           | 13Cr             |
| 14 | Handwheel          | A197             |
| 15 | Handwheel Lock Nut | A194 8M          |

## Dimensions

| Size   | L   | H   | W   | D    | Kg  |
|--------|-----|-----|-----|------|-----|
| 1/2"   | 79  | 160 | 100 | 10.5 | 1.5 |
| 3/4"   | 92  | 166 | 100 | 13.5 | 2.1 |
| 1"     | 111 | 198 | 125 | 17.5 | 2.8 |
| 1 1/2" | 120 | 253 | 160 | 29   | 5.0 |
| 2"     | 140 | 286 | 180 | 36   | 8.2 |

