

Cast Iron Knife Gate Valve - Unidirectional - Double Acting Actuator

To suit ANSI 150 and AGRI Standard Square Flanges, 4 Hole, Cast Iron Body, Stainless Steel Blade, NBR Gaskets, Fully Enclosed for Safety, with Position Indicator, Double Acting Hydraulic Actuator Operation

Material Specifications	
1. Body	EN GJL 250 Cast Iron
2. Blade	AISI 304 Stainless Steel
3. Ring	AISI 304 Stainless Steel
4. Gasket	HNBR
5. O-ring	NBR
6. Gland Packing	Fibre
7. Gasket	NBR
8. Stud	AISI 304 Stainless Steel
9. Gland Packing Box	EN GJL 250 Cast Iron
10. Washer	AISI 304 Stainless Steel
11. Nut	AISI 316 Stainless Steel
12. Position Indicator	Steel
13. Screw	AISI 304 Stainless Steel
14. Blade Connection	CW 614 N Brass
15. Nut	Zinc Plated Steel
16. Stem	CW 614 N Brass
17. Screw	AISI 304 Stainless Steel
18. Clamp	Zinc Plated Steel
19. Screw	AISI 304 Stainless Steel
20. Casing	PP
21. Tow Packing	Fibre
22. Cap	EN GJL 250 Cast Iron
23. Washer	AISI 304 Stainless Steel
24. Stuffing Box	CW 614 N Brass
25. Fork	CW 617 N Brass



Pressure / Temperature Specifications	
Pressure	PN10 6"
	PN8 8"
Temperature	-20°C to 90°C

Dimensions		
DN	6"	8"
Ø	150	200
H	801	954
h	667	795
S	60	60
F	M12	M12
A	150	180
D1	241.3	298.4
G	¾" UNC	¾" UNC
Kg	22.2	27.8

