

Solenoid Operated Gas Safety Shut-off Valve

Screwed BSPP, (2½" to 4" Available Flanged PN16,) Normally Closed, Automatic Reset, Power On, Class A EN161 & DIN3391-3394, IP54, 240V, For Natural Gas, LPG and Air.



Pressure / Temperature Specifications

Maximum Pressure	360 mBar
Temperature	-15°C to 60°C

Material Specifications

Body	Diecast Aluminium
Filter	AISI 303 Stainless Steel
Seal	NBR
Spring	AISI 302 Stainless Steel

Dimensions - BSPP

DN	A	B	C	D	Kg
⅜"	72	112	52	85	1.1
½"	72	112	52	85	1.1
¾"	86	156	70	96	2.2
1"	100	156	75	96	2.2
1¼"	150	214	110	118	5.0
1½"	150	214	110	118	5.0
2"	170	220	135	123	6.2
2½"	220	290	170	145	12.9
3"	220	290	170	145	12.8
4"	--	Confirm with Sales	--	--	--

Dimensions - Flanged PN16

DN	A	B	C	D	Kg
2½"	310	343	200	148	15.0
3"	310	343	200	148	15.3
4"	350	384	250	185	36.4

Capacity (m³/h at dp = 2.5 mBar)

DN	M³/h
⅜"	TBC
½"	6.4
¾"	14.8
1"	16.7
1¼"	38.5
1½"	47.1
2"	66.7
2½"	100.0
3"	150.0
4"	280.0

