

Brass Spring Check Valve + Strainer

Screwed **BSPP**, Brass Body, Acetal Disc, NBR Seat, with Fixed Stainless Steel Filter.

Pressure / Temperature Specifications	
Pressure	½" to 1" PN10
	1¼" to 2" PN8
	2½" & 4" PN6
Temperature	-10°C to 110°C

Material Specifications	
1. Body	Brass UNI EN 12165 CW617N
2. Disc	POM
3. Washers	NBR
4. Spring	Stainless Steel AISI 302
5. Filter Fitting	Nylon
6. Filter	Stainless Steel AISI 304 L

Dimensions							
G	D	H	A	F	B	X	Kg
½"	29	80	1mm²	1.0	2.0	30	0.11
¾"	37	90	1mm²	1.0	2.0	30	0.12
1"	44	100	1mm²	1.0	2.0	30	0.18
1¼"	56	110	1mm²	1.0	2.0	30	0.27
1½"	63	126	1mm²	1.0	2.0	30	0.33
2"	78	146	1.7mm²	1.25	2.6	16	0.56
2½"	103	162	1.7mm²	1.25	2.6	16	1.05
3"	120	188	1.7mm²	1.25	2.6	16	1.6
4"	155	214	1.7mm²	1.25	2.6	16	2.58

