

Brass Ball Valve - Screwed NPT - Locking Lever

Screwed NPT, Nickel Plated Brass Body, PTFE Seat, Red PVC Coated Steel Lever (Locking Lever 1/2" to 2")

Pressure/Temperature Specifications	
Pressure	PN16 1/4" & 3/8"
	PN40 1/2" to 1"
	PN25 1 1/4" to 2"
Temperature	-20°C to 70°C 1/4" & 3/8"
	-20°C to 110°C 1/2" to 2"

Material Specifications	
1. Body	Nickel Plated Brass
2. Bonnet	Nickel Plated Brass
3. Seat	PTFE
4. Ball	Chrome Plated Brass
5. Stem	Brass
6. O-ring	NBR
7. Nut	Nickel Plated Brass
8. Handle	PVC Coated Steel

Note: 1/4" & 3/8" are not Nickel Plated.

Dimensions							
Size ØD	Ød	L	H	W	Ca	Cb	Kg
1/4"	10	43.5	40	83	11	11	0.14
3/8"	10	43.5	40	83	11	11	0.17
1/2"	15	59	50	97	17	16.5	0.2
3/4"	19	62	53	97	16	16	0.26
1"	23	72	61	114	18	18	0.43
1 1/4"	29	83	73	128	19	19	0.65
1 1/2"	38	101	79	128	23	23	1.0
2"	47	105	90	202	20	20	1.5

