

Brass Ball Valve - Screwed BSPP

LV 4100 / LV 4111

Screwed BSPP, Nickel Plated Brass Body, PTFE Seat, Red (LV4100) or Blue (LV 4111) PVC Coated Steel Lever

Pressure/Temperature Specifications	
Pressure	PN32 ¼" to 1¼"
	PN25 1½" & 2"
	PN30 2½" to 4"
Temperature	-20°C to 110°C

Material Specifications	
1. Body	Nickel Plated Brass
2. Bonnet	Nickel Plated Brass
3. Seat	PTFE
4. Ball	Chrome Plated Brass
5. Stem	Brass
6. Gland Packing	PTFE
7. Gland Nut	Nickel Plated Brass
8. Handle	Chrome Plated Steel
9. Handle Nut	Nickel Plated Brass

Dimensions							
Size ØD	Ød	L	H	W	Ca	Cb	Kg
¼"	8	40	41	82	10.5	10.5	0.11
⅜"	10	44	42	82	10.7	11.8	0.13
½"	13.5	47	46	82	10.6	12.1	0.16
¾"	18.5	53	49	82	11.0	13.0	0.22
1"	23	65	56	102	15.0	16.0	0.34
1¼"	29	73	67	121	14.5	15.0	0.55
1½"	37	81	71	121	15.2	15.7	0.73
2"	47	98	93	144	16.8	17.7	1.26
2½"	64	135	116	227	26.5	26.5	3.29
3"	75	150	123	227	26.5	26.4	4.29
4"	97	177	142	227	28.5	28.5	6.88

