

# Brass Ball Valve - Standard Pattern - NPT

LV 4172

Screwed NPT, Full Bore, Red PVC Coated Steel Lever



Pressure/Temperature Specifications		
Pressure	PN16	1/4" & 3/8"
	PN40	1/2"
	PN32	3/4" & 1"
	PN25	1 1/2" & 2"
Temperature	PN16	3" & 4"
	-20°C to 150°C	1/4" & 3/8"
	-20°C to 110°C	1/2" to 4"

Material Specifications		
	1/4" & 3/8"	1/2" to 4"
1. Body	Hpb57-3 Brass	CW 617 N Brass
2. Body End	Hpb57-3 Brass	CW 617 N Brass
3. Ball	Hpb57-3 Brass	CW 617 N Brass
4. Seats	PTFE	PTFE
5. O-ring	NBR	NBR
6. Stem	Hpb57-3 Brass	CW 614 N Brass
7. Lever	PVC Coated Steel	PVC Coated Steel
8. Screw	Steel	Steel

Dimensions						
DN	D	A	E	B	C	Kg
1/4"	10	43.5	11	40	83	0.13
3/8"	10	43.5	11	40	83	0.13
1/2"	14.5	48	13	47	80	0.16
3/4"	19	57	14	53	90	0.27
1"	24	69	16.5	58	90	0.39
1 1/2"	37	89	19	81	135	0.9
2"	47	109	22.5	94	160	1.43
3"	75	147	25	142	265	3.93
4"	94	177	29	160	265	6.34

