

Brass Ball Valve with Drain Plug



LV 4610 / LV 4614

Screwed BSPP, Full Bore,

LV4610 = Red Aluminium Lever

LV4614 = Red Butterfly Handle



Pressure / Temperature Specifications	
Pressure	PN15
Temperature	-10°C to 95°C

Material Specifications		
1.	Body	Nickel Plated Brass CW 617 N
2.	Body End	Nickel Plated Brass CW 617 N
3.	Ball	Chrome Plated Brass CW 617 N
4.	Seats	PTFE
5.	Gasket	PTFE
6.	Tow Packing	PTFE
7.	Stem	Brass CW 614 N
8.	Stuffing Box	Brass CW 614 N
9.	Nut	Zinc Plated Steel
10.	Lever/Handle	Aluminium
11.	Drain	Nickel Plated Brass CW 614 N
12.	Plug	Nickel Plated Brass CW 614 N
13.	O-ring	NBR
14.	O-ring	NBR

Dimensions							
Size	Ø	H	S	L	L1	F	Kg
½"	15	50	54	92	52	11	0.23
¾"	20	56	60	92	60	12	0.33
1"	25	93	70	115	60	15.5	0.48
1¼"	32	80.5	81.5	125	-	16	0.83
1½"	40	85	93	150	-	17.5	1.09
2"	50	92	107.5	150	-	17.5	1.64

