

Stainless Steel Pressure Reducing Valve - EPDM



LV 6140 (1-6 Bar) / LV 6141 (4-10 Bar)

Screwed BSPP, Direct Acting, 316 Stainless Steel Body, EPDM Seat, Adjustable Outlet
 Pressure between 1.0 to 6.0 Bar and 4.0 to 10.0 Bar, Complete with Gauge



Pressure/Temperature Specifications	
Pressure	PN25
Temperature	-15°C to 85°C

Material Specifications	
1. Gauge	Stainless Steel
2. Upper Cover	316 Stainless Steel
3. O-ring	EPDM
4. U-ring	EPDM
5. Piston	316 Stainless Steel
6. Sealing Spacer	EPDM
7. Shaft	316 Stainless Steel
8. Diaphragm	EPDM
9. Body	316 Stainless Steel
10. UH-ring	EPDM
11. N/A	
12. Spring	Steel
13. Lower Cover	316 Stainless Steel
14. Washer	Brass
15. Adjusting Stem	304 Stainless Steel

Dimensions				
Size	H	L	CV	Kg
½"	75	71	2.4	0.9
¾"	75	86	4.0	1.3
1"	81	90	6.5	1.6
1½"	115	115	13.0	2.9
2"	115	120	17.0	3.0

