

Brass Solenoid Valve - Normally Open - NBR Diaphragm

Screwed **BSPP**, Pilot Operated, Normally Open, 2/2 Way, Brass Body, **NBR** Diaphragm, 12-24-48-110-230V AC & 12-24V DC



Pressure Specifications (Bar)							
Size	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
Minimum	0.1	0.1	0.2	0.2	0.4	0.4	0.4
Maximum	15.0	15.0	15.0	12.0	12.0	10.0	10.0

Temperature Specifications	
Temperature	-20°C to 90°C

Kv Values							
Size	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
Kv	2.6	3.5	5.8	9.5	12.5	31.0	45.0

Dimensions							
F.F	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
ØDN	11.5	13.5	18.0	26.0	32.0	45.0	50.0
L.F	11.5	14.0	13.5	17.5	21.5	22.5	24.0
CH.	24.0	28.0	34.0	42.0	53.0	62.0	73.0
L1	31.5	37.0	39.5	49.5	57.0	72.0	77.3
L2	25.5	30.7	34.5	43.5	54.5	66.0	67.7
L	57.0	67.7	74.0	93.0	111.5	138.0	145.0
ØA	41.5	45.0	54.0	71.0	86.6	110.0	121.0
H1	81.0	85.0	88.0	95.7	124.9	133.1	138.9
H	93.0	99.0	104.0	116.7	151.4	163.1	175.4

