

Primary Shut-off Valve

RIV 412

Brass Body, Hose Connection, NBR O-rings & Gaskets, EPDM and PEDH Ball

Pressure / Temperature Specifications

Pressure	3 Bar
Temperature	0°C to 60°C

Material Specifications

1	Screw	Stainless Steel AISI 304
2	Washer	Stainless Steel AISI 304
3	Hose Connection	Brass CB 754 S
4	Hex Screw	Stainless Steel AISI 304
5	O-ring	NBR
6	Body	Brass CB 754 S
7	O-ring	NBR
8	Plug	Brass CW 614 N
9	O-ring	NBR
10	Plug	Brass CW 617 N
11	Gasket	NBR
12	Gasket	NBR
14	Screwed Ring	Brass CB 754 S
15	Hex Screw	Stainless Steel AISI 304
16	O-ring	NBR
17	Ring	Steel
18	Ball	EPDM (wood core)
19	Ball	PEDH
20	Basket	PP
21	Rivet	Brass CW 614 N
22	Bracket	Stainless Steel AISI 430

Dimensions

DN	45mm	50mm	60mm	75mm	80mm
H	346	346	346	406	406
L	119	119	126	147	149
B	50	50	50	52	52
D	133	133	133	168	168
h1	133	133	133	140	140
h2	180	180	180	192	192
Kg	4.9	4.88	4.87	7.62	7.28

