

Brass Solenoid Valve - Combined Acting 2/2

Screwed BSP, Combined Acting, Normally Closed, 2/2 Way, Brass Body, NBR Diaphragm, 24V AC, 110V AC, 230V AC & 24V DC



Pressure / Temperature Specifications

Minimum Pressure	0
Maximum Pressure 3/8" to 3/4"	12 Bar (AC)
	12 Bar (DC)
Maximum Pressure 1"	10 Bar (AC)
	6 Bar (DC)
Temperature	-10°C to 90°C

Material Specifications

1. Body	CW617N Brass
2. Armature Tube	AISI 303 Stainless Steel
3. Plunger & Core	430Fr Stainless Steel
4. Springs	AISI 302 Stainless Steel
5. Seal	NBR

Dimensions

Size	A	B	C
3/8"	98	46	58
1/2"	98	46	58
3/4"	109	56	78
1"	122	74	95

Additional Information

Size	Orifice	KV	Coil Type
3/8"	13mm	2.2	3600
1/2"	13mm	2.5	3600
3/4"	19mm	5.5	3600
1"	25mm	10.2	3600

Coil Information

Voltage	Width	AC VA Inrush	AC VA Holding	DC Watt	Standard
24V DC	36mm	-	-	24	DIN 43650A
24V AC	36mm	30	24	-	DIN 43650A
110V AC	36mm	30	24	-	DIN 43650A
230V AC	36mm	30	24	-	DIN 43650A

